



SEACOR

Environmental Products

4" x 6" Foam-Filled Boom

Total Height	10 in.	254 mm
Draft	6 in.	152 mm
Freeboard	4 in.	102 mm
Buoyancy-to-Weight Ratio	6.0:1	
Flotation Element	Solid Polyethylene Foam	
Flotation Shape	Cylindrical - 4 in. diameter	101 mm
Flotation Length	6 ft.	1.8 m
Total Weight	0.8 lbs/ft	1.1 kg/m
Ballast	3/16 in. galvanized chain	4.76 mm
Fabric	22 oz Vinyl coated polyester	
Tensile Strength	500 lbs/inch	90 kg/cm
Tear Strength	150 lbs.	68.1 kg
Temperature Range	-30 to 140 F	-40 to 60 C
Section Length	100, 50, or 25 ft.	30.5, 15.2, or 7.6 m
Total Tensile Strength (actual ASTM method F-1093-91)	1,800 lbs	816 kg
Stowage Volume	18 cu.ft/ 100 ft	.17 cu. m/10m
Color	yellow or orange	
Cleaning	industrial detergents, steam, pressure wash, etc.	
Wind	10 knots	5.1 m/sec
Waves	Minor waves/calm water	

SEACOR Environmental Products

Phone: +1-206-378-4100 · Fax: +1-206-378-4103

U.S. Toll-Free Phone: 1-866-644-3677 · U.S. Toll-Free Fax: 1-866-655-3677

P.O. Box 3535 · Seattle, WA 98124-3535 USA