



# SEACOR

## Environmental Products

### 6" x 11" Foam-Filled Boom

Total Height	17 in.	432 mm
Draft	11 in.	280 mm
Freeboard	6 in.	152 mm
Buoyancy-to-Weight Ratio	2.5:1	
Flotation Element	Solid Polyethylene Foam	
Flotation Shape	Rectangular	
Flotation Length	4.5 ft.	1.37 m
Total Weight	1.2 lbs/ft	1.8 kg/m
Ballast	3/16 in. galvanized chain	.5 mm
Total Tension Member	3/16 in. coated cable	.5 mm
Fabric	22 oz Vinyl coated polyester	
Tensile Strength	500 lbs/inch	90 kg/cm
Tear Strength	150 lbs.	68.1 kg
Temperature Range	-30 to 140 F	-34 to 60 C
Section Length	100 or 50 ft.	30.5 or 15.2 m
Total Tensile Strength (actual ASTM method F-1093-91)	5,800 lbs	2631 kg
Stowage Volume	13 cu.ft/100 ft	.13 cu.M/10 m
Color	Yellow or orange	
Cleaning	Industrial detergents, steam, pressure wash, etc.	
Waves	2-3 ft.	.75 m
Wind	10-15 knots	5.1-7.7 m/sec

SEACOR Environmental Products

Phone: +1-206-378-4100 · Fax: +1-206-378-4103

U.S. Toll-Free Phone: 1-866-644-3677 · U.S. Toll-Free Fax: 1-866-655-3677

P.O. Box 3535 · Seattle, WA 98124-3535 USA