



SEACOR

Environmental Products

6" x 12" Foam-Filled Boom

Total Height	18 in.	457 mm
Draft	12 in.	305 mm
Freeboard	6 in.	152 mm
Buoyancy-to-Weight Ratio	6.4:1	
Flotation Element	Solid Polyethylene Foam	
Flotation Shape	Cylindrical - 6 inch diameter	152 mm
Flotation Length	6 ft.	1.83 m
Total Weight	1.7 lbs/ft.	2.5 kg/m
Ballast	1/4 galvanized steel chain	6.35 mm
Fabric	22 oz Vinyl coated polyester	
Tensile Strength	500 lbs/inch	90 kg/cm
Tear Strength	150 lbs.	68.1 kg
Temperature Range	-30 to 140 F	-34 to 60 C
Section Length	50 or 100 ft.	15.2 or 30.5m
Total Tensile Strength (actual ASTM method F-1093-91)	5,000 lbs	2,273 kg
Stowage Volume	33 cu. ft. per 100 ft.	.3 cu M/10m
Cleaning	Industrial detergents, steam, pressure wash, etc.	
Color	Yellow or orange	
Wind	15-20 Knots	7.7-10.3 m/sec
Wave Height	3 ft.	.9 m

SEACOR Environmental Products

Phone: +1-206-378-4100 · Fax: +1-206-378-4103

U.S. Toll-Free Phone: 1-866-644-3677 · U.S. Toll-Free Fax: 1-866-655-3677

P.O. Box 3535 · Seattle, WA 98124-3535 USA