



# SEACOR

## Environmental Products

### 6" x 6" Foam-Filled Boom

|                           |                               |                       |
|---------------------------|-------------------------------|-----------------------|
| Total Height              | 12 in.                        | 305 mm                |
| Draft                     | 6 in.                         | 152 mm                |
| Freeboard                 | 6 in.                         | 152 mm                |
| Buoyancy-to-Weight Ratio  | 6.5:1                         |                       |
| Flotation Element         | Solid Polyethylene Log        |                       |
| Flotation Shape           | Rolled Microfoam              |                       |
| Fabric Weight             | 23 oz./yd <sup>2</sup>        | 775 gm/m <sup>2</sup> |
| Ballast                   | 1/4 galvanized steel chain    | 6.35 mm               |
| Fabric                    | Polyurethane Coated Polyester |                       |
| End Connector             | Aluminum Universal            |                       |
| Handles                   | 2 per section                 |                       |
| Temperature Range         | 32 to 122 F                   | 0 to 50C              |
| Section Length            | 100 ft.                       | 30.5 m                |
| Combined Tensile Strength | 33,000 lbs.                   | 15,000 kg             |
| Color                     | Yellow, orange                |                       |
| Wind                      | 20 Knots                      | 10 m/sec              |
| Wave Height               | 2 ft.                         | .6 m                  |

SEACOR Environmental Products

Phone: +1-206-378-4100 · Fax: +1-206-378-4103

U.S. Toll-Free Phone: 1-866-644-3677 · U.S. Toll-Free Fax: 1-866-655-3677

P.O. Box 3535 · Seattle, WA 98124-3535 USA