



# SEACOR

## Environmental Products

### 8" x 12" Foam-Filled Boom with Top Cable

Total Height	20 in.	508 mm
Draft	12 in.	305 mm
Freeboard	8 in.	203 mm
Buoyancy-to-Weight Ratio	5.7:1	
Flotation Element	Solid Polyethylene Foam	
Flotation Shape	Cylindrical - 7 in. diameter	178 mm
Flotation Length	6 ft.	1.83 m
Total Weight	2.2 lbs/ft	3.3 kg/m
Ballast	5/16 in. galvanized steel chain	8 mm
Top Tension Member	1/4 in. stainless steel cable	6 mm
Fabric	22 oz Vinyl coated polyester	
Tensile Strength	500 lbs/inch	90 kg/cm
Tear Strength	150 lbs.	68.1 kg
Temperature Range	-30 to 140 F	-34 to 60 C
Section Length	50 or 100 ft.	15.4 or 30.5m
Total Tensile Strength (actual ASTM method F-1093-91)	6,400 lbs.	2,909 kg
Stowage Volume	40 cu. ft/ 100 ft	.37 cu. m/ 10m
Cleaning	Industrial detergents, steam, pressure wash, etc.	
Color	Yellow or orange	
Wind	20 Knots	10.3 m/sec
Wave Height	4 ft.	1.25 m

SEACOR Environmental Products

Phone: +1-206-378-4100 · Fax: +1-206-378-4103

U.S. Toll-Free Phone: 1-866-644-3677 · U.S. Toll-Free Fax: 1-866-655-3677

P.O. Box 3535 · Seattle, WA 98124-3535 USA