



# SEACOR

## Environmental Products

### PetroBarrier

Model	PetroBarrier 24"	PetroBarrier 36"
Freeboard	11 in. (279 mm)	12 in. (304 mm)
Draft	13 in. (330 mm)	24 in. (608 mm)
Standard Length	100 ft. (30.5 m)	100 ft. (30.5 m)
End Connectors	Non-Corrosive Universal Slide	Non-Corrosive Universal Slide
Weight	4.6 lbs/ft. ( )	7.0 lbs/ft. ( )
Buoyancy	9.84 lbs/ft ( )	13.66 lbs/ft ( )
Excess Buoyancy	114%	95%
Flotation	Closed cell foam jacketed in high density polyethylene shells	
Ballast Material	Lead weights with nylon through bolts	
Ballast Weight	1/2 lb./ft ( )	1 lb./ft. ( )
Barrier Material	PVC Double impregnated polyester chord belting with UV and Marine Growth inhibitors	
Tensile Strength	36,000 lbs. (16329 kg) Belting 8,000 lbs. (3628 kg) Working	54,000 lbs. (24493 kg) Belting 10,000 lbs. (4535 kg) Working
Grab Tensile Strength	1,500 lbs./in. ( )	1,500 lbs./in. ( )
Tear Strength	1,500 lbs. (680 kg)	1,500 lbs. (680 kg)
Fire Resistance	Barrier Material is Self Extinguishing	
Storage Volume	1.6 ft.3/ft ( )	2.5 ft.3/ft ( )
Perimeter	52.3 inches (1.33 m)	74.3 inches (1.89 m)
Operating Environment	Harbor	Harbor - Offshore

SEACOR Environmental Products

Phone: +1-206-378-4100 · Fax: +1-206-378-4103

U.S. Toll-Free Phone: 1-866-644-3677 · U.S. Toll-Free Fax: 1-866-655-3677

P.O. Box 3535 · Seattle, WA 98124-3535 USA