



SEACOR

Environmental Products

Open Top Fluid Reservoir with Floating Collar

Model	Capacity			Collapsed Size		Weight		Outside Diameter		Inside Diameter		Height		Outlets, 3"
	(gal)	(m ³)	(l)	(in)	(cm)	(lbs)	(kg)	(ft)	(m)	(ft)	(m)	(ft)	(m)	
CF 500	500	1.9	1883	15x20x40	38x56x106	40	18	7.6	2.3	5.1	1.5	3	.9	2
CF 1000	1000	3.8	3785	15x22x44	38x56x112	67	30	9.5	2.9	7	2.1	3	.9	2
CF 1500	1500	5.7	5700	15x22x48	38x56x122	90	40	10.8	3.3	7	2.1	3.3	1.0	2
CF 2000	2000	7.6	7600	19x24x48	48x61x122	120	54	12	3.7	7.8	2.4	3.5	1.1	2
CF 2500	2500	9.5	9500	16x30x50	41x76x127	135	62	13.2	4.0	9.0	2.7	3.5	1.1	2
CF 3000	3000	11.4	11,365	21x29x40	53x74x100	143	65	14.2	4.3	10.0	3.0	3.5	1.1	2
CF 4000	4000	15.2	15,141	25x35x45	64x89x115	160	74	16.2	4.9	12.0	3.7	4.5	1.1	2
CF 25,000	25,000	94.7	94,700	-	-	294	133	32.5	10	26.0	8.0	5	1.5	4
CF 50,000	50,000	189.4	189,400	-	-	401	182	45	13.7	38.6	11.8	5	1.5	4
CF 100,000	100,000	378.8	378,800	-	-	561	255	61.6	18.8	55	16.8	5	1.5	4

SEACOR Environmental Products

Phone: +1-206-378-4100 · Fax: +1-206-378-4103

U.S. Toll-Free Phone: 1-866-644-3677 · U.S. Toll-Free Fax: 1-866-655-3677

P.O. Box 3535 · Seattle, WA 98124-3535 USA