



SEACOR

Environmental Products

Model 55 Vacuum for Flammable Liquid

GSA Specifications	NSN-7910-00-632-9840
Operating Weight w/o tools / hose	150 lbs (68 kg)
Noise Level	Below 80 dbA, meets OSHA standards
Container Size	55 Gallon drum with 2" (50 mm) drain valve
Liquid Cutoff	Auto vac cutoff prevents overfilling
Construction Materials	Carbon steel
Finish	2-part epoxy, safety red and yellow
Wheels	Four 4" (100 mm) swivel casters, static conductive, (2) locking
Recovery Rates	Over 1 gallon per second
Inlet Size	Stainless Steel 1 1/2" (38 mm) with snap closures
Compressed Air Power	Single jet venturi with variable orifice
Compressed Air Required	35 SCFM at 60 PSIG
Compressor Required	10 HP minimum
Compressed Air Connection	Requires 1/2" (13 mm) NPTM fitting (minimum line size with no restrictions smaller than 1/2")
Tool Kit	Includes 25' (7.6 m) x 1 1/2" (38 mm) static conductive, fuel resistant vacuum hose with adapter, two bend floor wand, squeegee floor tool and crevice tool.
Minimum Width (90° from clamps)	24" (610 mm)
Maximum Width (across clamps)	28" (711 mm)
Overall Height	45" (1143 mm)

SEACOR Environmental Products

Phone: +1-206-378-4100 · Fax: +1-206-378-4103

U.S. Toll-Free Phone: 1-866-644-3677 · U.S. Toll-Free Fax: 1-866-655-3677

P.O. Box 3535 · Seattle, WA 98124-3535 USA